

GO PROGRAM Prescriptive HVAC Incentive Application Form Toll Free Hotline: 844-371-6704



MINIMUM EFFICIENCY LEVELS/ INCENTIVE LEVELS Table 1: Air Conditioning Systems					
Air Cooled Unitary and Split (new condenser and new coil) Air Conditioning Systems					
Equipment Capacity (Tons)	Equipment Capacity (Btuh)	Minimum SEER/EER	Maximum Incentive (\$/Ton)		
< 5.4 < 5.4 $\geq 5.4 \text{ to } < 11.25$ $\geq 11.25 \text{ to } < 20$ $\geq 20 \text{ to } < 63$ ≥ 63	< 65,000 Split < 65,000 Packaged ≥ 65,000 to < 135,000 ≥ 135,000 to < 240,000 ≥ 240,000 to < 760,000 ≥ 760,000	15.0 SEER/12.5 EER 15.0 SEER/12.0 EER 12.0 EER 12.0 EER 10.8 EER 10.2 EER	\$125 \$125 \$80 \$80 \$50 \$50		
Variable Refrigerant Flow Multi-Split Air Conditioning Systems					
Equipment Capacity (Tons)	Equipment Capacity (Btuh)	Minimum SEER/EER	Maximum Incentive (\$/Ton)		
< 5.4 Tons	< 65,000 Btuh	15.0 SEER/12.5 EER	\$175/Ton		

Table 2: Air Cooled Heat Pump Systems					
Equipment Capacity (Tons)	Equipment Capacity (Btuh)	Minimum SEER/EER	Maximum Incentive (\$/Ton)		
< 5.4 < 5.4 ≥ 5.4 to < 11.25 ≥ 11.25 to < 20 ≥ 20	< 65,000 Split < 65,000 Packaged ≥ 65,000 to < 135,000 ≥ 135,000 to < 240,000 ≥ 240,000	15.0 SEER/12.5 EER & 9.0 HSPF 15.0 SEER/12.0 EER & 8.5 HSPF 11.5 EER 11.5 EER 10.5 EER	\$125 \$125 \$80 \$80 \$50		
Variable Refrigerant Flow Multi Split Heat Pump Systems					
< 5.4 Tons	< 65,000 Btuh	15.0 SEER/12.5 EER & 9.0 HSPF	\$175/Ton		
Water Source Heat Pump Systems					
Equipment Capacity (Tons)	Equipment Capacity (Btuh)	Minimum SEER/EER	Maximum Incentive (\$/Ton)		
< 11.25	< 135,000	14.0 EER	\$80		
High Efficiency Energy Star [®] Mini-Split Pump Systems					
BTU Size Range	Minimum SEER	Minimum HSPF	Incentive		
9,000 to 18,000	18	12	\$1,000/Unit		

Table 3: Energy Saving Control and Fan Motor Options (When installed with new, qualifying equipment)					
Air Cooled Unitary and Split (new condenser and new coil) Air Conditioning Systems					
Type of Measure	Additional Information	Incentive			
Dual Enthalpy Economizer	Outside air economizer utilizing 2 enthalpy sensors (1 for outdoor and 1 for return air)	\$250/Unit			
Demand Control Ventilation	Outside air intake controled based on CO2 sensor	\$200/Unit			
Electronically Commutated Motors (ECMs) for HVAC Fans	ECMs installed on fan powered terminal boxes, fan coils or HVAC supply fans on small unitary equipment	\$150/Motor			